

# Category Data sheet



Dunnage bags, also known as air bags or inflatable bags, are used to secure and stabilize cargo during transportation. They are placed between or around items to fill empty spaces, preventing movement, shifting, or damage during transit.

For more details about various material and sizes please contact us.

[www.technotex.nl](http://www.technotex.nl)



## Features

- Cargo protection
- Prevents shifting
- Cost-effective solution
- Time-saving
- Often reusable or recyclable

## About us

Technotex is a Dutch manufacturer with over 30 years of experience in the manufacturing of lifting and lashing equipment.

As of January 2024, all Unifixx products are being supplied from the central warehouse in Coevorden, where Technotex is located.

## Technical data

level	gap (cm)	size	working pressure	load capacity	load capacity both sides
1	30.5	90x180	0.2 bar	2.59 ton	5.18 ton
2	30.5	90x180	0.34 bar	4.41 ton	8.81 ton
3	30.5	90x180	0.55 bar	7.13 ton	14.26 ton
4	30.5	90x180	0.68 bar	8.81 ton	17.63 ton
5	30.5	90x180	0.68 bar	8.81 ton	17.63 ton

  

level	gap (cm)	size	burst pressure	load capacity	load capacity both sides
1	30.5	90x180	0.55 bar	7.13 ton	14.26 ton
2	30.5	90x180	1.17 bar	15.16 ton	30.33 ton
3	30.5	90x180	1.72 bar	22.29 ton	44.58 ton
4	30.5	90x180	2.06 bar	26.7 ton	53.4 ton
5	30.5	90x180	2.55 bar	33.05 ton	66.1 ton

## Other products

We are a manufacturer and supplier for multiple productgroups. We can be your one-stop-shop for anything lifting, lashing and height safety related.

*Click any of the images to be forwarded to our website*



- [www.technotex.nl](http://www.technotex.nl)
- [sales@technotex.nl](mailto:sales@technotex.nl)
- +31 (0) 524 515 114

Follow us  
for updates

