

Category Data sheet



Composite strap is used for securing heavy loads during transport. It offers high strength and flexibility, making it ideal for bundling, palletizing, and securing items in shipping. It is resistant to weather and shock, and safer to handle compared to steel strapping.

We also have hotmelt strapping available, feel free to ask us for that datasheet.

www.technotex.nl



Features

- High Strength and Durability
- Shock absorption
- Weather resistance
- Cost-effective
- Safe handling
- Light weight solution

About us

Technotex is a Dutch manufacturer with over 30 years of experience in the manufacturing of lifting and lashing equipment.

As of January 2024, all Unifixx products are being supplied from the central warehouse in Coevorden, where Technotex is located.

Technical data

width	bs in daN*	meter/coil	weight/coil	packaging
13mm	330/530	1100m	10.75 kg	2 per box / 180 per pallet
16mm	450/735	850m	10.5 kg	2 per box / 180 per pallet
16mm	575/820	600m	9.0 kg	2 per box / 180 per pallet
19mm	500/780	600m	8.5 kg	2 per box / 180 per pallet
19mm	600/885	650m	11.0 kg	2 per box / 180 per pallet
25mm	885/1335	500m	11.5 kg	2 per box / 180 per pallet
32mm	1500/2185	300m	11.0 kg	2 per box / 180 per pallet

*linear/system

Other products

We are a manufacturer and supplier for multiple productgroups. We can be your one-stop-shop for anything lifting, lashing and height safety related.

Click any of the images to be forwarded to our website



- www.technotex.nl
- sales@technotex.nl
- +31 (0) 524 515 114

Follow us
for updates

