

Category Data sheet



Hotmelt strap is used for securing light-weight to medium-weight loads during shipping and storage. It provides reliable tension and is commonly used for bundling, palletizing, and reinforcing boxes. Made from polyester and bonded with a hot melt adhesive, it offers flexibility, durability, and safe handling.

We also have composite strapping available, feel free to ask us for that datasheet.

www.technotex.nl



Features

- High Strength and Durability
- Weather resistance
- Cost-effective
- Safe handling
- Light weight solution

About us

Technotex is a Dutch manufacturer with over 30 years of experience in the manufacturing of lifting and lashing equipment.

As of January 2024, all Unifixx products are being supplied from the central warehouse in Coevorden, where Technotex is located.

Technical data

width	bs in daN*	meter/coil	weight/coil	packaging
13mm	390/565	1100m	7.5 kg	2 per box / 160 per pallet
16mm	450/645	850m	7.0 kg	2 per box / 160 per pallet
16mm	620/800	600m	6.5 kg	2 per box / 160 per pallet
19mm	570/835	600m	6.0 kg	2 per box / 160 per pallet
19mm	770/1020	500m	6.0 kg	2 per box / 160 per pallet
25mm	1050/1415	500m	9.0 kg	2 per box / 160 per pallet

*linear/system

Other products

We are a manufacturer and supplier for multiple productgroups. We can be your one-stop-shop for anything lifting, lashing and height safety related.

Click any of the images to be forwarded to our website



- www.technotex.nl
- sales@technotex.nl
- +31 (0) 524 515 114

Follow us
for updates

